



1.MATERIAL

HOUSING: HIGH-TEMP THERMOPLASTIC UL94V-0
 COLOUR:WHITE
 STOPPLE: HIGH-TEMP THERMOPLASTIC UL94V-0
 COLOUR:BLACK

CONTACTS: PHOSPHOR BRONZE
 2.PLATING:
 CONTACTS: 50u" Min NICKEL UNDER 3u" GOLD PLATING
 IN CONTACT 100u" TIN PLATING IN SOLDER AREA

3.ELECTRICA:
 OPERATING VOLTAGE:125V AC,RMS
 CURRENT RATING:1.5A
 INSULATION RESISTANCE:500 MEGOHMS MIN.
 OPERATING TEMPERATURE:-25°C~+60°C

4.PART NO:
 RJF1008-X08-00XS

G: Au GOLD FLASH in contact
 J: Au 3u" in contact
 B: BAG
 T: TRAY

CUSTOMER DRAWING

一般公差
 GENERAL TOLERANCE

X ±0.30
 .XV ±0.20
 .XX ±0.10
 ANGLES ±3°



东莞市红都电子科技有限公司
 DONG GUAN SHI HONG DU ELECTRONICS TECHNOLOGY CO., LTD

制图 (DR): Kevin 12/10/13 品名 (TITLE): RJ45 CONN (全塑防水头)

审核 (CHK): 料号 (PART NO): RJF1008-X08-00XS

批准 (APP): 比例 (SCALE): 1:1 单位 (UNITS): mm 张数 (SHEET): 1 OF 1 图幅 (SIZE): A4